SA-2A:

Automatic Horizontal Cutting Machine

About the Machine

The SA-2A is a fully automatic machine for the cutting and stacking of virgin, rebond, polyurethane, and open-cell PVC foam. Knife grinding attachment comes with motor suction for dust and debris.



10th Floor, No. 200 Jinshan Rd. Sec. 2, Taipei, Taiwan. Phone: 886-2-23956686 Fax: 886-2-23217266 Email: service@sunkistm.com.tw



Technical Data

Cutting Width: 2200 mm
Cutting Height: 1300 mm
Cutting Length: 2500 mm
Cutting Thickness: 2mm (min)
Clearance below bandknife: 1300 mm
Clearance above bandknife: 1300 mm
Stacking Height: 1300 mm

Cut Speed (on steel belt): 0-92 m/min

Cutting Angle: Adjustable 0-5 degrees

Bandknife Width: 32 mm

Blade Guide Width: 95 mm (teflon coating)
Grinding Wheel (cup): 100 mm (diameter)

Power Required: 9 Kw

Add-Ons

- Add pressure roller
- Add silicone spray for blade guide
- Increase cutting table length to: 3200 mm, 4200 mm, 6000 mm
- Increase cut height: 1400 mm
- Add vacuum chambers below the cutting table

FOR HEAVY DUTY FOAM:

- increase knife width to 50 mm
- change steel belt table to gear rack

To find out more, please visit https://www.foam-machinery.com.tw/